WHAT IS CLAIMED IS:

1   1.   A mobile terminal, comprising:

2   a multiple PIM functionality module enabling the

3   mobile terminal to synchronize with multiple remote servers

4   and provide multiple groups of data with respect to a PIM

5   application; and

                transceiver circuitry for communicating with the

multiple remote servers through a network;

1   2.   The mobile terminal of Claim 1, wherein the multiple

2   PIM functionality module includes a plurality of versions of

3   a PIM application, each of the plurality of versions of the

4   PIM application able to synchronize with one of the multiple

5   remote servers.

1   3.   The mobile terminal of Claim 2, wherein each of the

2   plurality of versions of the PIM application includes separate

3   synchronization data to enable synchronization with the

4   multiple remote servers.

1   4.   The mobile terminal of Claim 1, wherein the multiple

2   PIM functionality module provides for a separate display

3   format of data from each of the multiple remote servers.

1   5.   The mobile terminal of Claim 4, wherein the separate

2   display format is user selectable.

1   6.   The mobile terminal of Claim 1, wherein the multiple

2   PIM functionality module provides for a unified display of

3   data from each of the multiple remote servers.

1   7.   The mobile terminal of Claim 1, wherein the multiple

2   PIM functionality displays a calendar containing the multiple

3   groups of data.

1   8.   The mobile terminal of Claim 7, wherein the multiple

2   groups of data may be displayed in bolded or non-bolded format

3   depending on a relevance of the data.

1   9.   The mobile terminal of Claim 7, wherein the multiple

2   PIM functionality enables selectable configuration of the

3   calendar.

1   10.   The mobile terminal of Claim 1, wherein the multiple

2   PIM functionality module further enables the mobile terminal

3   to synchronize with a second mobile terminal.

4   11. A mobile terminal, comprising:

5   a multiple PIM functionality module including a

6 plurality of versions of a PIM application, each version of

7 the PIM application able to synchronize with one of a

8 plurality of remote servers using synchronization data

9 contained therein; and

10   transceiver circuitry for communicating with the

11 plurality of remote servers through a wireless network.

1   12. The mobile terminal of Claim 11, wherein the

2 multiple PIM functionality module provides for a separate

3 display format of data from each of the multiple remote

4 servers.

1   13. The mobile terminal of Claim 12, wherein the

2 separate display format is user selectable.

1   14. The mobile terminal of Claim 11, wherein the

2 multiple PIM functionality module provides for a unified

3 display of data from each of the multiple remote servers.

1   15.   The mobile terminal of Claim 11, wherein at least

2 one version of the PIM application enables synchronization

3 with a second mobile terminal.

1   16.   A method of synchronizing a mobile terminal with a

2   plurality of remote servers, comprising the steps of:

3   obtaining synchronization between a first portion of

4   a PIM functionality and a first remote server to display data

5   from the first remote server;

6   obtaining synchronization between a second portion

7   of the PIM functionality and a second remote server to display

8   data from the second remote server; and

9   displaying the data from the first and second remote

10 servers on at least one display associated with the mobile

11 terminal.

1   17. The method of Claim 16, wherein the step of

2   displaying comprises the step of selectively displaying data

3   from either the first remote server or the second remote

4   server responsive to user input.

1   18. The method of Claim 16, wherein the step of

2 displaying further comprises the step of displaying the data

3 from the first and the second remote servers in a unified

4 display.

1   19. The method of Claim 16, wherein the step of

2 displaying further comprises the step of displaying the data

3 in a calendar.

1   20. The method of Claim 19, wherein the step of

2 displaying the data further comprises the step of displaying

3 the data in a bold format and a non-bolded format depending on

4 a type of the data.

1   21. The method of Claim 16, wherein the step of

2 displaying the data further comprises the step of displaying

3 the data in the calendar in accordance with a selectable

4 configuration of the calendar.

1   22.   A mobile terminal comprising:

2   a multiple PIM functionality module enabling the

3 mobile terminal to synchronize with multiple remote servers

4 and display multiple groups of data from the multiple remote

5 servers in a calendar; and

6   communication circuitry for communicating with the

7 multiple remote servers.

1   23.   The mobile terminal of Claim 22, wherein the

2 multiple groups of data may be displayed in bolded or non-

3 bolded format depending on a relevance of the data.

1   24.   The mobile terminal of Claim 22, wherein the

2 multiple PIM functionality enables selectable configuration

3 of the calendar.

1   25.   A method of synchronizing a mobile terminal with a

2   second mobile terminal, comprising the steps of:

3   obtaining synchronization between a first portion of

4   a PIM functionality and the second mobile terminal to display

5   data from the second mobile terminal; and

6   displaying the data from the second mobile terminal

7   on at least one display associated with the mobile terminal.

1   26.   The method of Claim 25, further including the steps

2   of:

3   obtaining synchronization between a second portion

4   of the PIM functionality and a remote server to display data

5   from the remote server; and

6   displaying the data from the remote server on the at

7   least one display associated with the mobile terminal.

1   27.   The method of Claim 25, further including the steps

2 of:

3   uploading data from the mobile terminal to the

4 second mobile terminal; and

5   displaying the data from the mobile terminal at the

6 second mobile terminal.